


FETS

高温波纹管

High-temperature corrugated conduit



+200°C
-80°C

	min.				max.
温度范围 <i>Temperature range</i>					
柔韧性 <i>Flexibility/Ductility</i>					
动态性能 <i>Dynamic</i>					
机械保护性能 <i>Mechanical protection</i>					
防火性能 <i>Fire precaution performance</i>					
耐化学性 <i>Chemical resistance</i>					
耐候性 <i>Resistance to weathering</i>					

材料: **ETFE**

FETS 由高技术高分子材料ETFE制成，提供了非常优异的耐高温及耐化学品性能。这种材料制成的管子适用于非常广的领域，比如化学工业及有耐高温要求的领域。

Material: ETFE

FETS corrugated conduit made of the high-tech polymer material ETFE, allows very high application temperatures and offer excellent chemical resistance. The material and conduit characteristics suit for extensive application areas like chemical process technology as well as for different high temperature requirements.

FETS

产品性能 / Product performances


应用性能 / Application performances	特性 Characteristics	单位 Unit	规范标准 Standards, specifications	备注 Remark
温度范围 Temperature range	-80 到 +200 -80 to +200	°C	IS FIP	
防火性能 / Fire safety performances				
不含卤素和镉 Free from halogens and cadmium	含 / no			
阻燃等级 Fire classification	V0		UL 94	
产品防火特性 Fire characteristic of the product	自熄 self-extinguishing		UL 1696	
易燃性 Flammability	自熄 self-extinguishing		FMVSS 302	
耐候性 / Weathering performances				
UV及耐候性 UV and weathering performance	优异 excellent		IS FIP	> 50 年 > 50 years

测试条件参照EN ISO 139温度23°C, 湿度 / 50% (如未注明测试条件)。IS FIP=FIP内部测试规范
Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated different). IS FIP = Internal Specification FIP

产品号 Part No.	名义尺寸 Nominal width	波型 Profile	尺寸 (mm) Dimensions in mm (nom.)		弯曲半径 (mm) Bending radius in mm	包装单元 PU
黑色 / black	NW		内径 / ID	外径 / OD	stat. R.	m
FETSX-07B.50	07	X	7,0	9,8	15	50
FETSX-10B.50	10	X	9,9	13,0	25	50
FETSX-12B.50	12	X	12,5	16,0	35	50
FETSX-17B.50	17	X	16,8	21,5	40	50
FETSX-23B.50	23	X	23,8	28,8	45	50
FETSX-29B.25	29	X	27,8	32,5	55	25
FETSX-36B.25	36	X	36,4	42,7	60	25
FETSX-48B.25	48	X	47,4	54,4	70	25

关于产品库存, 交期, 尺寸及颜色等问题请联系我们本地的经销商或客服。
Please contact our local distribution partner or our customer service regarding product availability, lead time, other sizes and colours.

产品代码 / Number code:



X = 特殊波型 / X = Special profile

弯曲半径 / Bending radius

stat. R = 静态安装最小弯曲半径
lowest recommended bending radius for static (fixed) installation

dyn. R = 动态安装最小弯曲半径
lowest recommended bending radius for dynamic (flexible) installation

我们尽我们的知识水平所提供的数据, 图像和技术规格图反映了当前的工程技术水平。这并不包含对最后应用有关的任何责任。产品用户需根据应用进行自己的评估, 以确定产品是否符合特殊的应用条件。我们对产品的责任只考虑一般规定条件下的水平。FIP保留对产品数据和数值进行技术调整的权力。例如更改材料和加工工艺, 在保证产品性能数值不下降的情况下不会另行通知。

The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.