

FIPLOCK® 标准波纹管编码规则

Part numbering key FIPLOCK® corrugated conduits

1 2 3 4 5 6
F **PAS** **C** - **23** **B** . **50**

1 型号 / Model

- F** = FIPLOCK® 标准壁厚波纹管
FIPLOCK® standard weight
- H** = FIPLOCK® 中等至厚壁型波纹管
FIPLOCK® medium to heavy weight
- L** = FIPLOCK® 轻型波纹管
FIPLOCK® light weight

2 材料 / Material type

- PAN** = PA6 MOD
- PAS** = PA6 MOD BS
- PAF** = PA6 MOD V0
- PAC** = PA6 MOD BS C
- PDA** = PA12 MOD ESD
- PDS** = PA12 MOD BS
- PDR** = PA12 MOD R
- PPO** = PP MOD
- PPS** = PP MOD BS
- PPS-U** = PP MOD BS UV

3 波型 / Profile

- F** = 细波型(匹配 FIPLOCK® ONE)
Fine profile (compatible with FIPLOCK® ONE)
- C** = 粗波型(匹配 FIPLOCK® ONE)
Coarse profile (compatible with FIPLOCK® ONE)

4 公称尺寸 / Nominal width (NW)

- 07-48** = NW Standard
- 56-125** = NW XL

5 颜色 / Colour

- B** = 标准黑色
Standard black
- G** = 标准灰色
Standard grey
- U** = UV-黑色
UV black
- 02** = 橙色 RAL2003
Orange similar to RAL2003
- A3** = 蓝色 RAL5015
Blue similar to RAL5015

6 包装单元 (PU) / Packing units (PU)

- 50** = 每卷长度或件数
Coil length or length of pieces
- A** = 特殊包装单元
Individual packing units

